Data sheet for three-phase Squirrel-Cage-Motors ABB																			
Motor	type:				FS: S	44959	5 - p - 300) hp -											
Client order no.							Item-No.					Offer	Offer no.						
Order no. Co							Consignme	nt no.					Proje	Project					
Remarks	Remarks																		
Electri	cal data																		
U	A / X/	f	Р	Р	n		l Load	[Amps]		Nom. Eff Load [d [%]	Pwr.	Factor Lo	ad [%]	d [%] Torque		T _k /T _N
[V]	Δ/Υ	[Hz]	[HP]	[kW]	[rpm]	4/4	3/4	1/2	0	LRC	4/4	3/4	2/4	4/4	3/4	2/4	[lb-ft]	LRT [%]	BDT [%]
		60	300.00	225.00															
Fram	ie Type: S4	4955			Type of	constr.	:		Motor Pro				t.: NEMA			Des.: S.F.: 1.15			
	Vtr. WT: lb	s	1	nsulation (Class.:Stan	dard Cla	ass F Insulation Temp. Rise Cl.				Cl.: B Amb. Temp.: + 40 to -20 °C				C @1000 m kVA: IP 55				P 55
Mecha	nical d	ata																	
Sound	level (SPI	. / SWL) a	at 60 Hz				dB(A)/dB	(A)		Thicke	ner								
		C 25(Octave Ba			ncies H 000	lertz 4000	8000	U-	Safe Stall Time Hot							S		
S	21 @ 3	250	50		00 2	000	4000	8000	Hz dB(A)	Safe Stall Time Cold							S		
	SPL@3 dB(A)								Frame material										
	nt of iner		b				Lb-ft ² Lb ft ²			Color, paint shade Coating (paint finish) S					Standard Paint - RAL7030 Standard Alkyed + Epoxy (C2)				
Bearin	d Inertia	Сарарш	ty.				LD IL								2	tandard A	ікуеа + і	Epoxy (C	_2)
	-	-									Ventilation Type								
Bearing DE NDE Bearing Type Bearing								Method of cooling Direction of rotation											
Bearing_Type Ball Bearing AFBMA:							inig	Fan Material											
Grease									VFD CT: VT:										
Capacity oz							oz Space heaters						-1-						
Grease									Brake:				-1-						
Termi	nal box																		
Lead Wire Connection Terminal box position																			
Voltage L1 L2 L3 Connected together							Material of terminal box												
										Cable	entry					-/-			
										_									
Notes:																			
$M_A/M_N = 10$	ed rotor curr ocked rotor to reak down to	orque / torq	ue nominal								s valid only 1 power / at 1		ration with r	notor desig	n IC411				
M ₄ /M ₄ = break down torque / nominal torque Responsible department Technical reference Created by							Approved by			Technical data are subject to change! There may be discrepancies									
· ·	N LVM SPC																		
Document type							Docı			Docu	customer				ner				
Datasheet Document title 1LE2421-4GB1												Released Document number							
					o I							Revis	ion C	reation date	e	Langu	age Pa	ae	
© ABB 2024											01			- 03 21:23	-	1/			

			Main ter	minal diagram					
Transmittal, reproduct	ion, dissemination and/or	editing of this document as well as	utilization of its contents and cor	nmunication thereof to others with	hout expre	ess authorization	are prohibited. Offenders will	be held liable fo	r payment of
damages. All rights cre	ated by patent grant or re	editing of this document as well as gistration of a utility model or design	gn patent are reserved.						, -,
Responsible depart	ment	Technical reference	Created by	Approved by	Technico	al data are subj	ect to change! There may en calculated and rating	Link docum	ents
IN LVM			,	Created automatically	be discre plate val	epancies betwe lues.	en calculated and rating		
	Document type Document status								
		Wiring diagramm	Released						
		number							
	1LE2421-4GB1 WDS-240503-212344								
Restricted						Revision	Creation date	Language	Page
© Innomotics	2024					AA	2024-05-03	en	1/1
		ļ				<u>I</u>	I	!	