<u>Data</u>	sheet	for th	nree-p	hase S	Squirre	el-Ca	ge-Mo	tors A	<u>BB</u>											
Motor	type:				FS: S	4495	6 - p - 350) hp -												
Client order no.							Item-No.					Offer	Offer no.							
Order no.							Consignme	nt no.					Proje	Project						
Remarks	Remarks																			
Electri	cal data																			
U	A / \/	f	Р	Р	n		l Load	[Amps]			Nom. Eff Load [9			Pwr.	Factor Lo	ad [%]	d [%] Torque		T _k /T _N	
[V]	Δ/Υ	[Hz]	[HP]	[kW]	[rpm]	4/4	3/4	1/2	0	LRC	4/4	3/4	2/4	4/4	3/4	2/4	[lb-ft]	LRT [%]	BDT [%]	
		60	350.00	260.00																
Frame Type: S449SS Type of constr.					: 			Motor Pro				t.: NEM/			Des.: S.F.: 1.15					
1	Mtr. WT: lb	S	l Ir	nsulation (Class.:Stan	dard Cla	ass F Insulation Temp. Rise Cl.:				Cl.: B Amb. Temp.: + 40 to -20 °C @1000 m				00 m	kVA: IP 55			P 55	
Mechanical data																				
Sound	level (SPI		at 60 Hz Octave Ba	nd Conta	r Fragua		dB(A) / dB	(A)		Thicke		Hot								
		25				000	4000	8000	Hz	Safe Stall Time Hot Safe Stall Time Cold						S				
SI	PL@3								dB(A)	Frame material				S						
Momer	nt of iner	tia					Lb-ft²								Standard Paint - RAL7030					
Ext Loa	d Inertia	Capabili	ty:				Lb ft²			Coating (paint finish) Standard Alkye						lkyed + I	Epoxy ((22)		
Bearin	gs									Ventil	ation Ty	pe								
Bearing	g DE ND	E								Method of cooling										
Bearing_Type Ball Bearing							ring	Direction of rotation												
AFBMA	:									Fan Material										
Grease						I	VFD						CT: VT:							
Capacity oz						OZ		Space heaters				-1- -1-								
Grease Type:						Brake:														
Termi	nal box																			
Lead Wire Connection Terminal box position																				
Voltage L1 L2 L3 Connected together							Material of terminal box													
							Cable	entry					-/-							
										_										
Notes:	1																			
$M_A/M_N = 10$	ed rotor curr ocked rotor to reak down to	orque / torq	ue nominal								s valid only 1 power / at 1		ration with r	notor desig	n IC411					
Responsible department Technical reference Created by							Approved by			Technical data are subject to change! There may be discrepancies					liscrepancies					
IN LVN																				
Document type Datasheet Document type												Document status custo				ner				
												Released								
Document title 1LE2421-4GB2											Document number									
											Revis	ion Ci	reation date	e	Langua	age Pa	ge			
© ABB 2024										01	2	024-05-	06 14:31	en	1/					

[Main ter	minal diagram]		
Transmittal, reproduct	ion, dissemination and/or	editing of this document as well as gistration of a utility model or desig	utilization of its contents and cor	nmunication thereof to others wit	hout expre	ss authorization	are prohibited. Offenders will	be held liable f	or payment of	
damages. All rights cre	ated by patent grant or re	gistration of a utility model or desig	gn patent are reserved.							
Responsible depart	ment	Technical reference	Created by	Approved by	Technica	ıl data are subj	ect to change! There may en calculated and rating	Link docum	ients	
IN LVM				Created automatically	be discre plate val	pancies betwe ues.	en calculated and rating			
		Document type				Document	itatus			
	Wiring diagramm Released Document title Document number									
		1LE2421-4GB2				WDS-240506-143149				
Restricted						Revision	Creation date	Language	Page	
© Innomotics	2024					AA	2024-05-06	en	1/1	
	_ >	I				l	1	1	1,	