Data sheet for three-phase Squirrel-Cage-Motors ABB																				
Moto	r type:				FS: -	p - hp	-													
Client order no. Item-No.									Offer no.											
Order no.						onsignme	nt no.					Proje	Project							
Remarks																				
<u> </u>	Electrical data																			
Electri	ical data	a																		
U Δ/Υ f [Hz] [H			P [HP]	P [kW]	n [rpm]		1	[Amps]			Nom. Eff Load [%						Torque	T <sub>A</sub> /T <sub>N</sub> T <sub>k</sub> /T <sub>N</sub>		
[۷]		[112]	[IIIF]	[KVV]	[ipiii]	4/4	3/4	1/2	0	LRC	4/4	3/4	2/4	4/-	3/4	2/4	[lb-ft]	LRT [%]	BDT [%]	
Frame Type: Type of constr.:												Motor Prot	.:		NEMA	Des.:	S.F.	: 1.15		
Mtr. WT: lbs				Insulation Class.:				Temp Rise Cl · R An			Amb. Temp.: + 55 to °C @1000 m					kVA: IP IP65				
	IVICI. VVI. II				Ilisulatio	// Class			Temp. Rise Cl.: B Amb. Temp.: + 55				+ 33 to	, to C @ 1000 m KVA:				IF IFOS		
Mech	anical d	lata																		
Sound	Sound level (SPL / SWL) at 60 Hz dB(A) / dB(A) Thickener																			
					er Freque					Safe S	Safe Stall Time Hot s									
_		250	50	00 10	000 2	000	4000	8000	Hz	Safe Stall Time Cold							S			
S	SPL@3								dB(A)	Frame	Frame material cast iron									
Mome	Moment of inertia Lb-ft <sup>2</sup>									Color, paint shade										
Ext Loa	ad Inertia	Capabilit	ty:				Lb ft²			Coating (paint finish) Standard Alkyed + Epoxy (C2)							2)			
Bearin	ngs									Ventilation Type										
Bearin	g DE   ND	ÞΕ								Method of cooling TEFC										
Bearin	g_Type							Ball Bea	ring	Direction of rotation										
AFBM/	۹:									Fan Material Polypropylen ESD										
Grease	e						·			VFD			CT: VT: 20:1							
Capacity oz						OZ		oz		Space heaters				-/-						
Grease Type:											Brake:					-/-				
Termi	inal box	,																		
	Lead Wir	re Connec	tion							Tormis	aal boy n	osition								
Volta	Voltage L1 L2 L3 Connected together								Terminal box position  Material of terminal box Cast Iron											
	vollage E1 L2 L5 Connected together								Cable entry -/-											
										Cable	entry					-/-				
Notes:		rent / curren	t nominal							3) Value i	s valid only	for DOL one	eration with r	notor de	sign IC411					
$M_A/M_N = I$	locked rotor	torque / torqu orque / nomi	ue nominal								d power / at				3.g. 1.c. 1 1 1					
Responsible department Technical reference Created by IN LVM SPC						d by		Approved by				Technical data are subject to char				ge! There may be discrepancies				
				Document type							1			Document status custor				r		
														Released						
Datasheet  Document title  1MB2121-2DC2.										Document number										
				лв2121-2DC2					_											
												on	Creation date	e	Languag	e Pag	je			
© ABB 2024											01		2024-05-	06 20:40	en	1/1	1			

			Main te	rminal diagram					
Transmittal, reproduc damages. All rights cr	tion, dissemination and/or eated by patent grant or r	r editing of this document as well a egistration of a utility model or des	is utilization of its contents and co	mmunication thereof to others wit	thout expres	s authorizatior	are prohibited. Offenders will	be held liable for	r payment of
Responsible depar	rtment	Technical reference	Created by	Approved by	Technical be discrep	data are subj pancies betwe	ect to change! There may en calculated and rating	Link docume	<u>ents</u>
IN LVM		Document time		Created automatically			ctatus	具機	
	Document type Document status Wiring diagramm Released								
		Document title		Document	number				
		1MB2121-2DC2					0506-204030		
Restricted		1			L	Revision	Creation date	Language	Page
© Innomotics	2024					AA	2024-05-06	en	1/1