Data sheet for three-phase Squirrel-Cage-Motors ABB																				
Motor	type:				FS: -	p - hp	-													
Client order no. Item-No.													Offer no.							
Order no.						C	Consignment no.						Project							
Remarks																				
<u> </u>	Electrical data																			
Electri	cal data	<b>a</b>																		
U Δ/Υ f [Hz] [Hz]			P [HP]	P [kW]	n [rpm]		I Load [Amps]				Nom. Eff Load [%]						Torque T <sub>A</sub> /T <sub>N</sub>		T <sub>k</sub> /T <sub>N</sub>	
[v]		[HZ]	[HF]	[KVV]	[rpiii]	4/4	3/4	1/2	0	LRC	4/4	3/4	2/4	4/4	1 314	2/4	[lb-ft]	LRT [%]	BDT [%]	
Frame Type: Type of constr.:											Motor Prot	.:		NEMA	Des.:	S.F.	: 1.15			
Mtr. WT: lbs				Insulation Class.:				Temp. Rise Cl.: B Amb				nb. Temp.: + 55 to °C @1000 m				kVA: IP IP65				
	1VICI. VV 1. II				Ilisulatio	// Class	Temp. Rise Ci.: B				mb. remp	+ 33 to	C @ 10		KV/	. IF IFOS				
Mech	anical d	lata																		
Sound	Sound level (SPL / SWL) at 60 Hz dB(A) / dB(A) Thickener																			
					er Freque					Safe Stall Time Hot s										
_		250	) 50	00 10	000 2	000	4000	8000	Hz	Safe Stall Time Cold							S			
S	PL@3								dB(A)	Frame material cas						ast iron				
Mome	Moment of inertia Lb-ft <sup>2</sup>								Color, paint shade											
Ext Loa	ad Inertia	Capabilit	y:				Lb ft²			Coating (paint finish) Standard Alkyed + Epoxy (C							2)			
Bearin	ıgs									Ventilation Type										
Bearing	g DE   ND	ÞΕ								Method of cooling TEFC										
Bearing	g_Type							Ball Bea	ring	Direction of rotation										
AFBM <i>A</i>	۸:									Fan Material Polypropylen ESD										
Grease										VFD	VFD CT: VT: 2					VT: 20:	1			
Capacity oz					oz		oz	Space heaters				-1-								
Grease Type:											Brake:					-/-				
Termi	nal box																			
	Lead Wir	re Connec	tion							Termir	aal boy n	osition								
Volta	Lead Wire Connection  Voltage L1 L2 L3 Connected together								Terminal box position  Material of terminal box Cast Iron											
	. s.a.ge E1 E2 E5 Connected together								Cable entry -/-											
										Cable	entry					-1-				
Notes:																				
I <sub>A</sub> /I <sub>N</sub> = loci	ked rotor cur	rrent / curren											ration with r	notor de	sign IC411					
		torque / torqi torque / nomi								2) at rate	d power / at	full load								
						Create SPC	Created by			Approved by			Technical data are subject to change! There				nay be di	iscrepancies		
IIN LV	ví			Docum	Document type						1			Document status custome				r		
												Released  Document number				•				
Datasheet  Document title  1MB2121-2DC2																				
				ив2121-2DC2																
													on	Creation date	e	Languag	e Pag	je		
© ABB 2024											01		2024-05-	05 06:34	en	1/1	1			

			Main te	rminal diagram					
				•					
Transmittal, reproduc damages. All rights cr	tion, dissemination and/or eated by patent grant or re	r editing of this document as well a egistration of a utility model or des	is utilization of its contents and co sign patent are reserved.	mmunication thereof to others wit	ithout expres	s authorization	are prohibited. Offenders will	be held liable for	r payment of
Responsible depar	tment	Technical reference	Created by	Approved by	be discre	data are subj pancies betwe	ect to change! There may en calculated and rating	Link docume	<u>ents</u>
IN LVM		Designation		Created automatically	plate valu			里/数	
	Document type Document status Wiring diagramm Released								
		Wiring diagramm  Document title	Document	aumhar	#P\$2				
		1MB2121-2DC2					number 0505-063436		
Restricted		- INIDZ 12 1-2DC2				Revision	Creation date	Language	Page
© Innomotics	2024					AA	2024-05-05	en	1/1