<u>Data</u>	sheet	t for th	ree-p	hase	Squirro	el-Ca	ge-Mot	ors A	<u>BB</u>											
Moto	r type:				FS: -	p-hp) -													
Client order no.							r Item-No.					Offer	Offer no.							
Order no.							Consignmer	nt no.					Proje	ct						
						· · · · J ·········														
Remarks	5																			
Electri	cal data	9																		
$\begin{array}{c c} U & f & P & P & n \\ \hline U & \Delta/Y & \hline U & I & \hline U & I & \hline U & I & I \\ \end{array}$				I Load [Amps]						Nom. Eff Load [%]			r. Factor Lo			T _A /T _N				
[V]		[Hz]	[HP]	[kW]	[rpm]	4/4	3/4	1/2	0	LRC	4/4	3/4	2/4	4/4	3/4	2/4	[lb-ft]	LRT [%] BDT [%]	
Frame Type: Type of constr.:					constr.:				Motor Pro				ot.: NEM			Des.: S.F.: 1.15		.: 1.15		
	Mtr. WT: I	bs			Insulation Class.:				Temp. R	Temp. Rise Cl.: B Amb. Temp.:			.: + 55 to '	+ 55 to °C @1000 m			kVA:		IP IP65	
Mach	anical d	lata																		
Sound	level (SP	L / SWL) a		1.0			B(A) / dB(A)			Thickener									
		250			er Freque 000 2	ncies He 1 000	ertz 4000	8000	Hz	Safe Stall Time Hot s										
s	PL@3								dB(A)	Safe Stall Time Cold						(s cast iron			
Mome	nt of iner	rtia					Lb-ft ²			Frame material										
		Capabili	iv:				Lb ft ²			Color, paint shade Coating (paint finish) Standard Alkyed + Epoxy (C2)								(2)		
Bearin										Coating (paint finish) Standard Alkyed + Epoxy (C2) Ventilation Type										
	g DE ND	DE						Method of cooling									TEFC			
	g_Type							Ball Bearing Direction of rotation				-								
AFBMA									-	Fan Material Polypropylen ESD										
Grease	e						I	VFD					CT: VT: 20:1							
Capaci	ty					oz		oz		Space	Space heaters				-1-					
Grease Type:										Brake:					-/-					
Termi	nal box	[
	Lead Wir	re Conne	tion							Termir	nal box p	osition								
Voltage L1 L2 L3 Connected together							ether	Material of terminal box Cast Iron												
							Cable entry -/-													
										_										
Notes:																				
$M_A/M_N = I$	locked rotor	rrent / curren torque / torq torque / nom	ue nominal								s valid only d power / at		eration with r	notor des	ign IC411					
Responsible department Technical reference Created by						Approved by			Techi	Technical data are subject to change! There may be discrepancies										
IN LVI	IN LVM SPC																			
Document type									F			Document status custome				ier				
				atasheet									Released Document number							
1MB2121-3BB1					B1															
									R			on	Creation date	2	Langua	ige Pa	ige			
© ABB 2024									01		2024-05-0	05 08:37	en en	1	/1					

[Main ter	minal diagram					
Transmittal, reproducti	on, dissemination and/or	editing of this document as well as	utilization of its contents and cor	nmunication thereof to others wit	hout expre	ss authorizatior	are prohibited. Offenders will	l be held liable fo	or payment of
aamayes. An rights cre	acco by patent grant of re	gistration of a utility model or desig	yn patent are feserveû.						
Responsible depart	ment	Technical reference	Created by	Approved by	be discre	pancies betwe	ect to change! There may en calculated and rating	Link docum	<u>ients</u>
IN LVM				Created automatically	plate val	lues.			
		Document type				Document s	status	500	
	Wiring diagramm Released								
		Document title			Document number WDS-240505-083712				
D. A. S. A.		1MB2121-3BB1							
Restricted © Innomotics	2024					Revision AA	Creation date 2024-05-05	Language	Page 1/1
	2024					<u> </u>	2024-03-03	en	