Data sheet for three-phase Squirrel-Cage-Motors ABB																				
Moto	r type:				FS: -	p - hp	-													
Client order no. Item-No.								Offe				fer no.								
Order no.						C	onsignme	nt no.					Project							
Remarks																				
<u> </u>	Electrical data																			
Electri	cal data	a																		
U Δ/Υ f [Hz] [I			P [HP]	P [kW]	n [rnm]		I Load [Amps]				Nom. Eff Load [%]			14 414 314 314			.		T _k /T _N	
[v]		[П2]	[HF]	[KVV]	[rpm]	4/4	3/4	1/2	0	LRC	4/4	3/4	2/4	4/4	1 314	2/4	[lb-ft]	LRT [%]	BDT [%]	
Frame Type: Type of constr.:											Motor Prot	.:		NEMA	Des.:	S.F.	: 1.15			
Mtr. WT: lbs			Insulation Class.:					Tamp Rise CL · R Amh				Temp.: + 55 to °C @1000 m				kVA: IP IP65				
	101C1. VV 1.11				Ilisulatio	// Class	: Temp. Rise Cl.: B An				mb. remp	+ 33 to	C @ 10		KV/	ν.	IF IFOS			
Mech	anical d	lata																		
Sound	Sound level (SPL / SWL) at 60 Hz dB(A) / dB(A) Thickener																			
					er Freque					Safe Stall Time Hot s										
_		250	50	00 10	000 2	000	4000	8000	Hz	Safe S	Safe Stall Time Cold						S			
S	PL@3								dB(A)	Frame material cast iron										
Mome	nt of iner	tia					Lb-ft²			Color, paint shade										
Ext Loa	ad Inertia	Capabilit	ty:				Lb ft²			Coating (paint finish) Standard Alkyed + Epoxy (C							2)			
Bearin	igs									Ventilation Type										
Bearin	g DE ND	ÞΕ								Method of cooling TEFC										
Bearin	g_Type							Ball Bea	ring	Direction of rotation										
AFBM/	۹:									Fan Material Polypropylen ESD										
Grease	е						·			VFD	VFD CT: VT: 20:1						1			
Capacity oz					OZ		OZ		Space heaters				-/-							
Grease Type:											Brake:					-/-				
Termi	nal box	,																		
	Lead Wir	re Connec	tion							Tormir	aal boy n	ocition								
Volta		L1		 L2	L3	 3	Conne	ected tog	ether	Terminal box position Material of terminal box Cast Iron										
l voita	Voltage L1 L2 L3 Connected together									Cable entry -/-										
										Cable	entry					-1-				
										-										
Notes:																				
$M_A/M_N = I$	locked rotor	rent / curren torque / torqu torque / nomi	ue nominal								s valid only d power / at		ration with r	notor de	sign IC411					
M _u /M _n = break down torque / nominal torque Responsible department Technical reference Created by IN LVM SPC							Approved by			Tech	Technical data are subject to change! The				iscrepancies					
	-			Docum	Document type								Docui	Document status customer						
					sheet									Released						
Document title												Document number								
					1MB2121-3BB1															
												on	Creation date		Languag	T				
© ABE	3 2024												01		2024-05-	03 04:33	en	1/1	1	

			Main te	rminal diagram					
Transmittal, reproduc damages. All rights cr	tion, dissemination and/or eated by patent grant or r	r editing of this document as well a egistration of a utility model or des	is utilization of its contents and co sign patent are reserved.	mmunication thereof to others wit	thout expres	ss authorization	n are prohibited. Offenders will	l be held liable fo	r payment of
D		I Total Control Control	I constitution	I	T	l d-4		Treatment	
Responsible depar	tment	Technical reference	Created by	Approved by Created automatically	be discre plate valu	i aata are subj pancies betwe ues.	iect to change! There may een calculated and rating	Link docum	<u>ents</u>
		Document type	<u> </u>	Created automatically	1	Document:	status		
Wiring diagramm Released									20.25
		Document title	Document	number					
		1MB2121-3BB1					0503-043349		
Restricted		1				Revision	Creation date	Language	Page
© Innomotics	2024					AA	2024-05-03	len	1/1