Data sheet for three-phase Squirrel-Cage-Motors ABB																				
Moto	r type:				FS: -	p - hp	-													
Client order no. Item-No.									Offer no.				no.							
Order no.						(onsignme	nt no.					Project							
Remarks																				
<u> </u>	Electrical data																			
Electri	ical data	a																		
U Δ/Y f [Hz]			P [HP]	P [kW]	n [rpm]		I Load [Amps]				Nom. Eff Load [%]						Torque T _A /T			
[۷]		[112]	[IIIF]	[KVV]	[ipiii]	4/4	3/4	1/2	0	LRC	4/4	3/4	2/4	4/-	3/4	2/4	[lb-ft]	LRT [%]	BDT [%]	
Frame Type: Type of constr.:											Motor Prot	.:		NEMA	Des.:	S.F.	: 1.15			
Mtr. WT: lbs			Insulation Class.:					Tamp Rise Cl · R Amh								kVA: IP IP65				
	IVICI. VVI. II				Ilisulatio		: Temp. Rise Cl.: B Amb.					mb. remp	Temp.: + 55 to °C @1000 m kV/				IF IF US			
Mech	anical d	lata																		
Sound	Sound level (SPL / SWL) at 60 Hz dB(A) / dB(A) Thickener																			
					er Freque					Safe S	Safe Stall Time Hot s									
_		250	50	00 10	000 2	000	4000	8000	Hz	Safe S	Safe Stall Time Cold						S			
S	SPL@3								dB(A)	Frame material cast iron						ast iron				
Mome	Moment of inertia Lb-ft ²								Color, paint shade											
Ext Loa	ad Inertia	Capabilit	ty:				Lb ft²			Coating (paint finish) Standard Alkyed + Epoxy (C2							2)			
Bearin	ngs									Ventilation Type										
Bearin	g DE ND	ÞΕ								Method of cooling TEFC										
Bearin	g_Type							Ball Bea	ring	Direction of rotation										
AFBM/	۹:									Fan Material Polypropylen ESD										
Grease	e						V				VFD CT: VT: 20:1									
Capacity oz					oz		oz		Space heaters				-/-							
Grease Type:											Brake:					-/-				
Termi	inal box																			
	Lead Wir	re Connec	tion							T										
Volta	Voltage L1 L2 L3 Connected together								Terminal box position Material of terminal box Cast Iron											
Voita	voltage L1 L2 L3 Confrected together								Cable entry -/-											
										Cable	entry					-1-				
										-										
Notes:																				
$M_A/M_N = I$	locked rotor	rent / curren torque / torqu torque / nomi	ue nominal								s valid only d power / at		ration with r	notor de	sign IC411					
Responsible department Technical reference Created by IN LVM SPC						ed by		Approved by			Tech		subject to cha	nge! There r	ge! There may be discrepancies					
<u> </u>				Document type						<u> </u>			Document status custo				r			
Datasheet												Released Document number								
Document title 1MB2121-3BE																				
					D2	2														
												Revision Creation date		e	Languag	e Pag	je			
© ABB 2024											01		2024-05-	19 15:32	en	1/1	1			

			Main te	rminal diagram					
Transmittal, reproduc damages. All rights cr	tion, dissemination and/or	r editing of this document as well a egistration of a utility model or des	is utilization of its contents and co	mmunication thereof to others wit	thout expres	s authorization	are prohibited. Offenders will	l be held liable for	r payment of
Responsible depar	tment	Technical reference	Created by	Approved by	Technical be discre	l data are subj pancies betwe	ect to change! There may een calculated and rating	Link docume	<u>ents</u>
IN LVM		D		Created automatically	plate valu	ies.		具(後)	
	Document type Document status Wiring diagramm Released								
		Wiring diagramm Document title		Document	number	200			
		1MB2121-3BD2)519-153215		
Restricted		-				Revision	Creation date	Language	Page
© Innomotics	2024					AA	2024-05-19	en	1/1