Data sheet for three-phase Squirrel-Cage-Motors ABB																				
Moto	r type:				FS: -	p - hp	-													
Client order no. Item-No.									Offer no.											
Order no.						C	onsignme	nt no.					Project							
Remarks																				
	Electrical data																			
Electri	ical data	3																		
U Δ/Υ f [Hz]			P [HP]	P [kW]	n [rpm]	4/4	1	[Amps]		100	Nom. Eff Load [%						.	T <sub>A</sub> /T <sub>N</sub> T <sub>k</sub> /T <sub>N</sub>		
["		[112]	[,,,]	[KW]	[ibiii]	4/4	3/4	1/2	0	LRC	7/-	317	217	-1/-	314	2/4	[lb-ft]	LRT [%]	BDT [%]	
Frame Type: Type of constr.:											Motor Prot	.:		NEMA	Des.:	S	i.F.:			
Mtr. WT: lbs				Insulation Class.:				Temp. Rise Cl.: B								kVA: IP IP65				
	IVILI. WI.II	us			IIISUIAU	on Class.:	.: Temp. Ris				e Cl.: B Amb. Temp.: + 40 to °C @100				100 III	KVA. IP IPOS				
Mech	anical d	lata																		
Sound	level (SP	L / SWL) a	nt 60 Hz			dE	B(A) / dB	(A)		Thicke	ner									
		C	ctave Ba	nd Cente	er Freque	ncies He	rtz			Safe Stall Time Hot s										
		250	50	00 10	000 2	000	4000	8000	Hz	Safe Stall Time Cold							s			
S	PL@3								dB(A)	Frame material						С	ast iron			
Mome	Moment of inertia Lb-ft <sup>2</sup>								Color, paint shade											
Ext Loa	ad Inertia	Capabilit	ty:				Lb ft²			Coating (paint finish)  Standard Alkyed + Epoxy (0							оху (С	2)		
Bearin	ngs									Ventilation Type										
Bearin	g DE   ND	E								Method of cooling TEFC										
Bearin	g_Type							Ball Bea	ring	Direction of rotation										
AFBM <i>A</i>	۹:									Fan Material Polypropylen ESD										
Grease								VFD				CT: VT: 20:1								
						OZ		oz		Space heaters				-I-						
Grease Type:									Brake:					-I-						
Termi	inal box																			
	Lead Wir	re Connec	ction							Termir	nal box p	osition								
Volta	Voltage L1 L2 L3 Connected together								ether	Material of terminal box Cast Iron										
									Cable entry -/-											
									Cubic	circiy					,					
										-										
Notes:																				
$M_A/M_N = I$	locked rotor	rent / curren torque / torqu	ue nominal								s valid only d power / at		eration with r	notor de	sign IC411					
M <sub>e</sub> /M <sub>N</sub> = break down torque / nominal torque  Responsible department Technical reference Created by  IN LVM SPC						d by		Approved by				Technical data are subject to change! Ti				nay be di	iscrepancies			
				Document type						<u> </u>			Document status customer				r			
Datasheet													Released							
Document title												Document number								
				B2121-4DC5																
				7										on	Creation date	e	Languag	e Pag	je	
© ABB 2024											01		2024-05-	05 02:17	en	1/1	1			

			Main te	rminal diagram					
Transmittal, reproduc damages. All rights cr	tion, dissemination and/or eated by patent grant or re	r editing of this document as well a egistration of a utility model or des	is utilization of its contents and co sign patent are reserved.	mmunication thereof to others wit	thout expres	s authorization	n are prohibited. Offenders will	l be held liable for	r payment of
Posnonsible donor	tmant	Tochnical reference	Created by	I Approved by	Tochnical	l data aro cubi	inst to shangal Thora may	Link docume	onto
Responsible depar	unent	Technical reference	Created by	Approved by Created automatically	be discrep	pancies betwe ues.	ect to change! There may een calculated and rating	LITIK GOCUME	ents
<u> </u>		Document type	<u>I</u>	Created automatically		Document :	status	製鋼	
Wiring diagramm Released									<b>33 33</b>
		Document title		Document	number				
		1MB2121-4DC5				WDS-240	0505-021726		
Restricted		1			İ	Revision	Creation date	Language	Page
© Innomotics	2024	İ				AA	2024-05-05	en	11/1