Data sheet for three-phase Squirrel-Cage-Motors ABB																				
Moto	r type:				FS: -	p - hp	-													
Client order no. Item-No.									Offer no.											
Order no.						C	onsignme	nt no.					Project							
Remarks								L												
<u> </u>	Electrical data																			
Electri	ical data	a																		
U Δ/Y f P P n [Hz] [HP] [kW] [rpm				f1					Nom. Eff Load [%]						.		T _k /T _N			
[V]		[П2]	[HF]	[KVV]	[thiii]	4/4	3/4	1/2	0	LRC	4/4	3/4	2/4	4/4	1 3/4	2/4	[lb-ft]	LRT [%]	BDT [%]	
Frame Type: Type of constr.:											Motor Prot	.:		NEMA	Des.:	S.F.	: 1.15			
Mtr. WT: lbs			Insulation Class.:					Temp. Rise Cl.: B Amb.)() m		VA: IP IP65				
	IVICI. VVI. II				IIISulatio		: Temp. Rise Ci.				Cl.: B Amb. Temp.: + to °C @1000 m				KV/	NVA. IF IFOS				
Mech	anical d	lata																		
Sound	Sound level (SPL / SWL) at 60 Hz dB(A) / dB(A) Thickener																			
					er Freque					Safe S	Safe Stall Time Hot s						S			
_		250	50	0 10	000 2	000	4000	8000	Hz	Safe S	Safe Stall Time Cold						S			
S	SPL@3								dB(A)	Frame	Frame material cast iron									
Mome	nt of iner	tia					Lb-ft²			Color, paint shade										
Ext Loa	ad Inertia	Capabilit	ty:				Lb ft²			Coatir	Coating (paint finish) Standard Alkyed + Epoxy (oxy (C	2)	
Bearin	ngs									Ventilation Type										
Bearin	g DE ND	ÞΕ								Method of cooling TEFC										
Bearin	g_Type							Ball Bea	ring	Direction of rotation										
AFBM/	۹:									Fan Material Polypropylen ESD										
Grease	e						·			VFD	VFD CT: VT: 20:1						I			
Capacity oz					OZ		oz		Space	Space heaters					-1-					
Grease Type:							'	Brake:	Brake:					-/-						
Termi	inal box																			
	Lead Wir	re Connec	tion							T										
Volta	Lead Wire Connection Voltage L1 L2 L3 Connected together							Terminal box position Material of terminal box Cast Iron												
Voita	voltage L1 L2 L3 Connected together							Cable entry -l-												
										Cable	entry					-1-				
Notes:																				
$M_A/M_N = I$	locked rotor	rent / curren torque / torqu torque / nomi	ue nominal								s valid only d power / at		eration with r	notor de	sign IC4 I I					
Responsible department Technical reference Created by SPC							Approved by			Tech	Technical data are subject to change! There ma				iscrepancies					
	-			Document type						<u> </u>			Document status customer							
					sheet									Released						
Document title 1MB2221-4DC1												Document number								
				C1																
												Revision Creation date		9	Languag	e Pag	e			
© ABB 2024											01		2024-05-0	08 07:44	en	1/1	l			

			Main te	rminal diagram					
Transmittal, reproduc damages. All rights cr	tion, dissemination and/or eated by patent grant or re	r editing of this document as well a egistration of a utility model or des	s utilization of its contents and co ign patent are reserved.	mmunication thereof to others wit	ithout expres	s authorizatior	are prohibited. Offenders will	l be held liable for	r payment of
		I=	T- ··	T	1			T	
Responsible depar	tment	Technical reference	Created by	Approved by	be discrep plate valu	l data are subj pancies betwe	ect to change! There may een calculated and rating	Link docume	<u>ents</u>
UN EVIVI		Document type	<u> </u>	Created automatically		Document	status	具数	
Wiring diagramm Released								700	20.5
		Document title	1	Document	number				
		1MB2221-4DC1			1		0508-074456		
Restricted		1			L	Revision	Creation date	Language	Page
© Innomotics	2024					AA	2024-05-08	len	1/1